

## DATASHEET

# EcoFlow PowerOcean (Three-phase)

## Home Solar Battery Solution

The innovative 3-phase solar battery solution starting from 5kWh, expandable at all times.

EcoFlow PowerOcean is a premium 3-phase modular home solar solution. With a flexible upfront investment, outstanding safety features, outage backup and super smart control, PowerOcean is designed to achieve power independence for the whole house.



### For installers

EcoFlow Pro Web Portal

<https://portal.ecoflow.com/pro/eu>




EcoFlow Pro App

### For users

EcoFlow Web Portal

<https://portal.ecoflow.com/user/eu>



EcoFlow App

## EcoFlow PowerOcean LFP Battery

Number of Battery Packs		EF BD-JC-S1 x 1 EF BD-5.1-S1 x 1 EF BD-B-S1 x 1	EF BD-JC-S1 x 1 EF BD-5.1-S1 x 2 EF BD-B-S1 x 1	EF BD-JC-S1 x 1 EF BD-5.1-S1 x 3 EF BD-B-S1 x 1
Performance	Battery Nominal Capacity (kWh)	5.1	10.2	15.3
	Battery Usable Capacity (95% Depth of Discharge) (kWh)	4.8	9.7	14.5
	Max. Output Power (W)	3300	6600	9900
	Max. Input Power (W)	2500	5000	7500
	Nominal Voltage (V)	800		
	Operating Voltage Range (V)	720-960		
	Battery Cell Type	LFP		
Compliance	Certificates	CE MARK		
	Safety Standard	EN62619, EN62040-1, EN62477-1, ISO13849, VDE-AR-E-2510-50		
	Delivery Standard	UN38.3		
	EMC	EN 61000-6-1, EN 61000-6-3		
General	Dimension (WxDxH) (Without Adjustable Feet) (mm)	680×183×612 (±1)	680×183×1009 (±1)	680×183×1406 (±1)
	Weight (kg)	65.6	120.9	176.2
	Installation	Floor stand		
	Operating Temperature (°C)	-20 to 50		
	Max. Operating Altitude (m)	3000		
	Cooling Method	Natural convection		
	Noise Level (dB)	≤35		
	Relative Humidity	0%-100% (Condensing)		
	Protection Level	IP65		
Protective Class	I			

# EcoFlow PowerOcean Hybrid Inverter

Technical parameters		EF HD-P3-6K0-S1	EF HD-P3-8K0-S1	EF HD-P3-10K-S1	EF HD-P3-12K-S1
DC Input (PV)	Maximum PV Power (W)	10000	12000	14000	16000
	Maximum Input Voltage (V)	160-1000			
	MPPT Operating Voltage Range (V)	200-850			
	Start-Up Voltage (V)	160			
	Nominal Input Voltage (V)	600			
	Maximum Input Current per MPPT (A)	16			
	Maximum Short Circuit Current per MPPT (A)	24			
	Number of Strings per MPPT	1			
	Number of MPPTs	2			
DC Input (Battery)	Overvoltage Category	II			
	Maximum Charging Power (W)	6000	8000	10000	12000
	Maximum Discharging Power (W)	6000	8000	10000	12000
	Maximum Continuous Charging Current (A)	12.5	12.5	12.5	15
	Maximum Continuous Discharging Current (A)	12.5	12.5	12.5	15
AC Input	Rated Voltage (V)	800			
	Maximum Battery Capacity (kWh)	45.9			
	Connection	3L+N+PE			
	Overvoltage Category	III			
	Nominal Apparent Power from Utility Grid (VA)	12000	16000	16000	16000
	Maximum Apparent Power from Utility Grid (VA)	12000	16000	16000	16000
	Rated Input Voltage (V)	230/400, 3L+N+PE			
AC Output (On-grid)	Maximum AC Current from Utility Grid (A)	17.4	23.1	23.1	23.1
	Nominal Frequency (Hz)	50/60			
	Grid Connection	3L+N+PE			
	Overvoltage Category	III			
	Nominal Apparent Power Output to Utility Grid (VA)	6000	8000	10000	12000
	Maximum Apparent Power Output to Utility Grid (VA)	6000	8000	10000	12000
AC Output (Backup)	Nominal Output Voltage (V)	230/400, 3L+N+PE			
	Nominal Frequency (Hz)	50/60			
	Maximum AC Current Output to Utility Grid (A)	8.7	11.5	14.4	17.4
	Nominal Output Current (A)	8.7	11.5	14.4	17.4
	Current Total Harmonic Distortion (At Rated Power)	<3%			
	Power Factor	-0.8...1...+0.8			
	AC Output (Backup)	Nominal Apparent Power (VA)	6000	8000	10000
Maximum Apparent Power (VA)		7200@1 sec	9600@1 sec	12000@1 sec	14400@1 sec
Nominal Output Voltage (V)		230/400, 3L+N+PE			
Nominal Frequency (Hz)		50/60			
Nominal Output Current (A)		8.7	11.5	14.4	17.4
Maximum Output Current (A)		10.4@1 sec	13.9@1 sec	17.4@1 sec	20.9@1 sec
Protection	Voltage Total Harmonic Distortion (At Linear Load & Rated Power)	<3%			
	Residual Current Monitoring	Integrated			
	PV Insulation Resistance Detection	Integrated			
	Anti-Islanding Protection	Integrated			
	PV Reverse Polarity Protection	Integrated			
	AC Overcurrent Protection	Integrated			
	Backup Load Short-Circuit Protection	Integrated			
	AC Overvoltage Protection	Integrated			
	DC Switch	Integrated			
	Remote Shutdown	Integrated			
Efficiency	Protective Class	I			
	Maximum Efficiency	97.6%			
Compliance	Maximum MPPT Efficiency	99.9%			
	Certificates	CE/CB/TUV MARK			CE MARK
	Safety Standards	IEC/EN62109-1, IEC/EN62109-2			
	Grid-tied Standards	EN 50549, EN50438, TOR Erzeuger Type A, EEA-NE7- CH, PTPIREE, UTE C 15-712-1, ANRE, O3E-323, G99, G98,CEIO-21, C10/11, VDE-AR-N-4105 EN 62311, EN 301 489-1, EN 301 489-17, EN IEC 61000-6-3, EN IEC 61000-3-2, EN 61000-3-3, EN IEC 61000-6-1, EN 300 328			
General Data	EMC				
	Topology	Non-isolated			
	Operating Temperature Range (°C)	-20 to 50			
	Storage Temperature (°C)	-30 to 60			
	Operating Relative Humidity	0%-100% (Condensing)			
	Noise Emission (dB)	<35			
	Maximum Operating Altitude (m)	3000			
	Weight (kg)	Approximately 29.6			
	Dimensions (WxDxH) (mm)	588x175x380 (±1) (without trim cover), 588x175x455 (±1) (with trim cover)			
	Protection Level	IP65			
	Self-Consumption at night (W)	<25			
	Cooling Method	Natural convection			
	Communication Method	RS485 (for Meter) & CAN (for BMS) & Wi-Fi & Bluetooth & WAN & 4G			
	Wi-Fi Frequency Range (MHz)	2412-2472 (20) / 2422-2462 (40),			
	Maximum Output Power (dBm)	18.54			
Bluetooth Frequency Range (MHz)	2402-2480,				
Maximum Output Power (dBm)	7.19				
Pollution Degree	PD3				
Environmental Category	Outdoor/Indoor				

Please be advised that EcoFlow reserves the right to modify the design, components, and specifications of its products at any time without prior notice or obligation. The actual product details and final design may vary from those shown or described in this brochure.